

CONSTRUCTION SAW

ACCESSORIES P.30

JTS-315LA-M

1000-022-495

- Perfect for a full-scale construction site and a small workshop as a universal circular saw
- With saw blade angle and cutting depth adjustment
- With extension table at rear, provides a 1'600 mm surface
- Zinc-plated steel sheet surface worktable
- Parallel fence can also be used as a mitre fence
- Two wheels and handles for easy transportation



TECHNICAL DATA

Motor (V/kW)	230/2.0
Blade speed (U/min)	2'950
Blade-size/bore (ø-mm)	315/30
Mitre capacity	0°-45°
Max. cutting depth at 0°/45° (mm)	83/60
Max. cutting width (mm)	290
Table size (mm)	800×550
Extension size (mm)	800×400
Dimensions (mm)	1'650×650×1'000
Weight (kg)	48

Other technical data and accessories you will find in the manual.

CONSTRUCTION SAW

ACCESSORIES P.30

JTS-315SP-M

1000-001-620

JTS-315SP-T

1000-001-759

- Foldable legs and bayonet mounted rear table extension facilitate quick machine start-up
- Powerful motor with brake, suitable for continuous operation
- Galvanized steel machine table withstands corrosion and wear
- Anodized aluminium table insert
- Sliding table with ball bearings moves accurately for straight and angled cuts
- Convenient blade tilt up to 47° via hand wheel, adjustable stop at 0°
- Transport device facilitates simple change of positions



TECHNICAL DATA

Model	JTS-315SP-M	JTS-315SP-T
Motor (V/kW)	230/2.2	400/3.1
Blade speed (U/min)	2'950	2'950
Blade-size/bore (ø-mm)	315/30	315/30
Mitre capacity	0 - 47°	0 - 47°
Max. cutting depth at 0°/45° (mm)	90/60	90/60
Max. cutting width (mm)	310	310
Table size (mm)	800×550	800×550
Extension size (mm)	800×550	800×550
Precision sliding table (mm)	250×230	250×230
Max. length of cut (mm)	600	600
Dimensions (mm)	2'050×970×1'000	2'050×970×1'000
Weight (kg)	69	69

Other technical data and accessories you will find in the manual.