

GRINDING

OSCILLATING SPINDLE SANDERS

Page 49

BELT/DISC SANDER

Page 52

OSCILLATING EDGE SANDER

Page 55

DRUM SANDERS

Page 56

DUAL DRUM SANDERS

Page 60

WETSTONE SHARPENER

Page 62

ACCESSORIES

Page 64

GRINDING



OSCILLATING SPINDLE SANDER

ACCESSORIES P.64

JBOS-5-M

1000-001-614

- 25mm oscillating action reduces friction heat to protect wood and prolong sleeve life
- Main spindle support runs on precision ball bearings and is oscillated by a heavy-duty worm and gear mechanism for consistent performance
- Oscillating gears run in a closed lubrication box for a long service life
- Powerful 0.7 kW induction motor easily handles the toughest sanding projects
- Large gray cast iron worktable for precise grinding of large workpieces, tiltable 45°



TECHNICAL DATA

Motor (V/kW)	230/0.7
Spindle speeds (rpm)	1'450
Spindle diameter (ø-mm)	6/12/16/38/50
Max. sanding height (mm)	100
Table size (mm)	370 x 370
Table tilt	0° - 45° down
Sanding spindle height (mm)	150
Oscillations/Minute	30
Oscillation stroke (mm)	25
Dust port (ø-mm)	100
Dimensions (mm)	440 x 430 x 530
Weight (kg)	35

Other technical data and accessories you will find in the manual.