

BELT/DISC SANDER

ACCESSORIES P.64

JSG-96-M

1000-001-515

- Large cast iron table has preset stops at 90° and 45° to let you use the belt sander vertically, horizontally or anywhere in between
- Exclusive dual thumbscrew belt tracking adjustment locks to keep belt on track during use
- Graphite covered steel platen runs cooler increasing machine and belt life
- Specially designed belt guard allows full use of the 150mm belt width and length
- Drive drum is rubber-coated for a better grip on the sanding belt resulting in less slippage



TECHNICAL DATA

Motor (V/kW)	230/1.0
Sanding disc speed (rpm)	1'400
Sanding belt speed (m/s)	10
Sanding disc diameter (ø-mm)	230
Sanding belt dimensions (mm)	150 x 1'220
Sanding disc table tilt	45° down
Sanding belt table tilt	45° down
Sanding disc table size (mm)	250 x 300
Sanding belt table size (mm)	140 x 280
Dust port (ø-mm)	100
Dimensions (mm)	780 x 420 x 730
Weight (kg)	41

Other technical data and accessories you will find in the manual.

BELT/DISC SANDER

ACCESSORIES P.64

JSG-233A-M

1000-001-892

- Two-in-one sanding station for sanding a variety of lengths and angles
- Beveling table top allows for sanding 45° - 90°
- Belt angle adjustment allows for sanding 0° - 90°
- Mitre fence allows double mitres to be sanded
- Simple, repeat changes of abrasive disc sheet using hook-and-loop disc
- Cast aluminum work table
- Low noise and low vibration



TECHNICAL DATA

Motor (V/kW)	230/0.55
Sanding disc speed (rpm)	1'850
Sanding belt speed (m/s)	8
Sanding disc diameter (ø-mm)	200
Sanding belt dimensions (mm)	100 x 914
Sanding disc table tilt	0° - 45°
Sanding belt table tilt	0° - 45°
Sanding disc table size (mm)	115 x 225
Sanding belt table size (mm)	25 x 125
Dust port (ø-mm)	100
Dimensions (mm)	500 x 450 x 350
Weight (kg)	26

Other technical data and accessories you will find in the manual.