PLANING/MILLING

DUST COLLECTION

## PLANER/THICKNESSER

ACCESSORIES P.86

JPT-260-M

000-001-910

JPT-260-T

1000-001-621

- Dual fold-out table to switch from planing to thicknessing in a
- matter of seconds, without removing the fence

  Graded planing tables made from high-quality cast iron
- guarantee outstandingly smooth workpiece movement
- The 3-knife shaft allows fast processing and top planing results
- Large-sized planer fence made from aluminium, inclinable to 45°, precisely machined, stable in operation
- Warp resistant one-piece machine casing for unfailing precision
- Feed can be turned off



## **TECHNICAL DATA**

Model	JPT-260-M	JPT-260-T
Motor (V/kW)	230/2.3	400/2.3
Cutterhead rotation (rpm)	5'300	5'300
Feed speed (m/min)	5.5	5.5
Maximum planing width (mm)	256	256
Thicknessing height (mm)	4 – 225	4 – 225
Maximum depth of cut (mm)	3	3
Maximum thicknessing depth of cut (mm)	4.5	4.5
Number of knives	3	3
Planer blades (mm)	260×25×3	260×25×3
Depth of cut table size (mm)	540×256	540×256
Planing table length (mm)	1'120	1'120
Minimum thicknessing length (mm)	150	150
Fence size (mm)	1'100×150	1'100×150
Fence tilt (deg.)	45°/90°	45°/90°
Dust port (ø-mm)	100	100
Dimensions (mm)	1'120×700×1'000	1'120×700×1'000
Weight (kg)	170	170

Other technical data and accessories you will find in the manual.

## PLANER/THICKNESSER

ACCESSORIES P.86

JPT-310-M

00-002-732

JPT-310-T

1000-001-783

- Dual fold-out table to switch from planing to thicknessing in a matter of seconds, without removing the fence
- Graded planing tables made from high-quality cast iron guarantee outstandingly smooth workpiece movement
- Two-sided eccentric regulation for quick adjustment of the chip remover and hollow joint
- The 3-knife shaft allows fast processing and top planing results
- Large-sized planer fence made from aluminium, inclinable to 45°, precisely machined, stable in operation
- Warp resistant one-piece machine casing for unfailing precision
- Feed can be turned off



## TECHNICAL DATA

Model	JPT-310-M	JPT310-T
Motor (V/kW)	230/2.9	400/2.9
Cutterhead rotation (rpm)	5'500	5'500
Feed speed (m/min)	7	7
Maximum planing width (mm)	307	307
Thicknessing height (mm)	4 – 225	4 – 225
Maximum depth of cut (mm)	3	3
Maximum thicknessing depth of cut (mm)	4.5	4.5
Number of knives	3	3
Planer blades (mm)	310×25×3	310×25×3
Depth of cut table size (mm)	540×307	540×307
Planing table length (mm)	1'400	1'400
Minimum thicknessing length (mm)	150	150
Fence size (mm)	1'100×150	1'100×150
Fence tilt (deg.)	45°/90°	45°/90°
Dust port (ø-mm)	100	100
Dimensions (mm)	1'400×750×1'000	1'400×750×1'000
Weight (kg)	230	230

Other technical data and accessories you will find in the manual.