

SPINDLE MOULDER

ACCESSORIES P.86

JWS-34KX-M

1000-001-851

JWS-34KX-T

1000-001-771

- Large cast iron router table, precision planed and polished
- Simple speed change with four speeds – 1'700/3'500/6'000/8'000rpm – via poly-v belt
- Spindle indexing for user-friendly tool changes
- Spindle height sc
- Collet chuck adapters 8mm and 12mm for using routing tools
- JET JOSS-S abrasive sleeves can be used to sand cambered pieces



TECHNICAL DATA

Model	JWS-34KX-M	JWS-34KX-T
Motor (V/kW)	230/1.9	400/2.9
Spindle speeds (rpm)	1'700/3'500/6'000/8'000	1'700/3'500/6'000/8'000
Max. tool diameter (ø-mm)	180	180
Max. tool height (mm)	70	70
Clamp height (mm)	70	70
Router bit collet size (mm)	8/12	8/12
Max. tool height above table (mm)	120	120
Spindle diameter (ø-mm)	30	30
Spindle travel (mm)	80	80
Table opening diameter (mm)	160	160
Table size (mm)	635 x 600	635 x 600
Dust port (ø-mm)	100	100
Dimensions (mm)	760 x 840 x 990	760 x 840 x 990
Weight (kg)	145	145

Other technical data and accessories you will find in the manual.

