DUST COLLECTION

GRINDING

MORTICER

ACCESSORIES P.98

719A-M

- Toothed rack height adjuster together with accurate dovetail guide and gas pressure balancer cylinder
- Powerful motor

1000-003-000

- End stops for precision batch productions
- Workpiece clamp with quick adjustment

Head can be turned by 180° for drilling a door lock Large-sized handwheels for easy adjustment of the jig table Enclosed base cabinet with storage compartment ■ Table tilt angle (719-AS-M) up to 35°

719-AS-M

TECHNICAL DATA

Model	719A-M	719-AS-M
Motor (V/kW)	230/1.3	230/1.3
Spindle speeds (rpm)	1'450	1'450
Maximum cutter size (hard/soft)	19×19/25×25	19×19/25×25
Max. bore size diameter (mm)	13	13
Max. workpiece height (mm)	195	195
Max. chisel stroke (mm)	200	200
Table travel along axes (longitudinal/transverse, mm)	400/100	400/100
Table tilt	-	0 – 35°
Table size (mm)	520×180	520×180
Dimensions of the workpiece stop (mm)	520×90	520×90
Centre of chisel to back fence (mm)	100	100
Dimensions (mm)	650×500×1'760	650×500×1'760
Weight (kg)	110	125

BENCHTOP DRILL PRESS

ACCESSORIES P.98

JWDP-12-M

DRILLING

- Heavy-duty drill press developed specifically for wood workshops
- Extra-large, precision-planed work table
- Large cast iron base for high stability
- Long-lasting, built-in LED work light reduces shadows
- Electric drill chuck protector, belt guard protection and emergency stop as standard



TECHNICAL DATA

Motor (V/kW)	230/0.55	
Spindle speed range (rpm)	440-2'580	
Spindle fixture	MT2	
Spindle travel (mm)	80	
Distance spindle to column (mm)	152	
Spindle distance to table (max., mm)	430	
Spindle distance to base (max., mm)	590	
Table size (mm)	243×243	
Table tilt	45° left/45° right	
Miter t-slot/distance (mm)	15×60	
Column diameter (mm)	65	
Dimensions (mm)	940×420×580	
Weight (kg)	38	

Other technical data and accessories you will find in the manual.

Other technical data and accessories you will find in the manual.