

BENCHTOP DRILL PRESS

ACCESSORIES P.98

JDP-15B-M

1000-004-074

JDP-15B-T

1000-022-547

- Heavy-duty drill press developed specifically for wood workshops
- Extra-large, precision-planed work table with 2 T-slots and 4 table slots for even greater flexibility
- Flat table edge designed for using clamps
- Replaceable MDF table insert
- Integrated drill depth stop for precision batch tasks
- Efficient 1.0 kW induction motor and quiet poly-v belt drive
- One-handed belt tensioning for fast speed changes
- Xacta-X laser system easily identifies the drill center
- Integrated long-life LED working lamp prevents shadows
- Large cast iron base for high stability
- Electric drill chuck protector, belt guard protection and emergency stop as standard



TECHNICAL DATA

Model	JDP-15B-M	JDP-15B-T
Motor (V/kW)	230/1.0	400/1.0
Spindle speed range (rpm)	180 – 2'900	180 – 2'900
Number of spindle speeds	16	16
Spindle fixture	MT2	MT2
Spindle travel (mm)	80	80
Distance spindle to column (mm)	190	190
Spindle distance to table (max., mm)	470	470
Spindle distance to base (max., mm)	680	680
Table size (mm)	320 x 454	320 x 454
Table tilt	90° left/90° right	90° left/90° right
Miter t-slot/distance (mm)	13/270	13/270
Column diameter (mm)	73	73
Dimensions (mm)	723 x 483 x 1'679	677 x 454 x 1'115
Weight (kg)	71	71

Other technical data and accessories you will find in the manual.

FLOORSTANDING DRILL PRESS

ACCESSORIES P.98

JDP-17-M

1000-004-075

JDP-17-T

1000-022-550

- Heavy-duty drill press developed specifically for wood workshops
- Extra-large, precision-planed work table with 2 T-slots and 4 table slots for even greater flexibility
- Flat table edge designed for using clamps
- Replaceable MDF table insert
- 127 mm drill stroke with just one turn of the handwheel, for long drill holes
- Integrated drill depth stop for precision batch tasks
- Efficient 1.0 kW induction motor and quiet poly-v belt drive
- One-handed belt tensioning for fast speed changes
- Xacta-X laser system easily identifies the drill center
- Integrated long-life LED working lamp prevents shadows
- Large cast iron base for high stability
- Electric drill chuck protector, belt guard protection and emergency stop as standard



TECHNICAL DATA

Model	JDP-17-M	JDP-17-T
Motor (V/kW)	230/1.0	400/1.0
Spindle speed range (rpm)	180 – 2'900	180 – 2'900
Number of spindle speeds	16	16
Spindle fixture	MT2	MT2
Spindle travel (mm)	127	127
Distance spindle to column (mm)	215	215
Spindle distance to table (max., mm)	763	763
Spindle distance to base (max., mm)	1'194	1'194
Table size (mm)	356 x 483	356 x 483
Table tilt	90° left/90° right	90° left/90° right
Miter t-slot/distance (mm)	13/270	13/270
Column diameter (mm)	80	80
Dimensions (mm)	723 x 483 x 1'679	723 x 483 x 1'679
Weight (kg)	86	86

Other technical data and accessories you will find in the manual.